

# Declaration of Performance

## GreenLine EPS 300

- 1. Unique identification code of the product-type:** SE-JP300RE-CPR-02
- 2. Type, batch pr serial number:** GreenLine EPS 300
- 3. Intended use or uses of the construction product:** Thermal insulation products for buildings (EPS)
- 4. Name and contact address of the manufacturer:** BEWI Insulation Sverige AB, Diabasvägen 11, SE-541 52 Skövde.
- 5. Where applicable, name and contact address of the authorised representative:**
- 6. System or systems of assessment and verification of constancy of performance of the construction product as set out in Annex V:** AVCP System 3
- 7. Notified Testing Laboratory and tasks performed:** Łukasiewicz – WIT, Laboratorium Materiałów Budowlanych „IZOLACJA”, nr 1454 has conducted ITT According to system 3.

8. Essential characteristics (EN 13163: 2012+A2:2016)	Performance	Note	
Thermal conductivity	$\lambda_D = 0,034 \text{ W/mK}$	EN 12667	
Thermal resistance – Thickness: 100 mm	$R_d=2,94$	(resistance $R_D$ )	
Compressive stress (10 % deformation)	$CS(10) = 300 \text{ kPa}$	ISO 29469	
Bending strength	450 kPa	Jf. annex C*	
Shear strength	225 kPa	Jf. annex F.3*	
Durability of compressive strength against ageing and degradation, Compressive creep (2%)	$CC = 90 \text{ kPa}$	EN 1606	
Long term water absorption by immersion	WL(T)5	EN/ISO 16535	
Watervapor transmission $\mu$	40 - 100	EN 10456	
Watervapor permeability $\delta \text{ mg}/(\text{Pa.h.m})$	0,006 - 0,015	Jf. annex F.4*	
Tolerances (T2)	Tolerances (mm)	Thickness product (mm)	
	-2		+2
Tolerances	Length	$\pm 3,0 \text{ (L3)}$	EN 13163
	Width	$\pm 3,0 \text{ (W3)}$	
	Thickness	$\pm 2,0 \text{ (T2)}$	
	Flatness	$\pm 30,0 \text{ (P30)}$	
	Squareness	$\pm 5,0 \text{ (S5)}$	
Fire class (Reaction to fire)	NPD	-	
Continuous glowing combustion	NPD	-	
Durability of thermal conductivity against heat, weathering, and ageing/degradation	No changes over time/NPD	-	
Durability of compressive strength ageing and degradation – Freeze-thaw resistance	NPD	-	
Durability of compressive strength ageing and degradation – Long term thickness reduction	NPD	-	
Tensile strength	NPD	-	
Deformation under specific load	NPD	-	
Acoustic absorption indexes	NPD (b)	-	

\*Reference to EN 13163: 2012+A2:2016

(a) Test method is not available

(b) EPS products have no significant airborne sound absorption properties

**9. The performance of the product listed above is in conformity with the declared performance in point 8. This declaration of performance is issued under the sole responsibility of the manufacturer, as noted above.**

Signed for and behalf of the manufacturer by:



Ahmad Nazal, QE Manager  
Skövde, 2026.03.20